SAHEED LAXMAN NAYAK MEDICAL COLLEGE AND HOSPITAL, KORAPUT

Tel.No.06852 252121

E-mail:slnmchkpt22@gmail.com

No. 5118 /2024

SHORT TENDER CALL NOTICE

Sealed tenders are hereby invited from the intending Authorized Firms/ Dealers having valid GST registration along with copies of GST Registration Certificate, PAN Card, Tax Clearance Certificate (updated GSTR-3B) and Manufacture Authorization Certificate for supply of Instruments and Equipment's to be used at Saheed Laxman Nayak Medical College & Hospital, Koraput. The Firms/ Dealers should quote their rate per unit as per Annexure-1 and tax separately.

The sealed quotation super scribed as "Short Tender Call Notice for supply of Instruments and Equipment's to be used at SLNMCH, Koraput" should reach the Office of the undersigned by 03.10.2024 at 5:30 PM through Speed post/ Regd. post/ Courier only. The tender received beyond the scheduled date and time will not consider under any circumstances. The sealed tender received by the undersigned will be opened on dt: 04.10-2321/at 12.30 PM. The tenderer/bidder or their authorized representatives are allowed to be present during the opening of the tenders, if they so like. The undersigned reserves the right to cancel/reject any or all the quotation without assigning any reason thereof. The successful bidder should deposit 10% of value of the contract/ purchase order as performance security deposit in favour of Medical Superintendent, SLN MCH, Koraput by way of Insurance Surety Bond, account payee demand draft, fixed deposit receipt or bank guarantee from any of the scheduled commercial banks. The performance security should be valid for 01 year from date of installation and will refundable without interest after 60 days of expiry of the contract/warranty. All legal disputes, if any relating to purchase, installation and commissioning etc. are subject to jurisdiction in the courts of law situated at Koraput. In the event of bidder fails to provide service for repair/ replace the respective items during the warranty period, the performance security will be forfeited.

Documents to be submitted

- 1. GST Details
- PAN
- Tax Clearance Certificate (updated GSTR-3B)
- Valid ISO/ISI/GMP certificate
- Manufacture Authorization Certificate

SLNMCH, Koraput

SI No.	Item Name	Specification	Quoted Price Per Unit (including GST)
01	Spot Light with stand	Size- 21 LED, Flexible arm for easy positioning and adjustment, Stable stand base for improved stability and safety, Adjustable brightness and colour temperature for optimal lighting condition, LED light source for efficient and long lasting lighting. Warranty – 01 year	
02	Sponge Holding Forceps		
03	Chittle Forceps with stand		
04	Artery Forceps 6"		
05	Tooth Forceps		
06	Non Tooth Forceps		
07	BP Handle 3.4 size	Manufacture should be WHO / GMP certified, The instrument	
08	Needle Holder 6"	steel should comply to EN ISO 7153 standard, Stainless steel materials grade should be ASI410 and 420 certified and should	
09	Stitch Cutter Scissor 6"	be supported by test report, Instrument should cover 1 year	d
10	Mayo Scissor 6"	replacement warranty, all the instruments should be	
11	Kidney Tray (Medium)	autoclavable.	
12	Bowel- 2 piece		
13	Protoscope Adult & Paediatrics		
14	Allis Forceps		
15	Plain Forceps		
16	Needle and Syringe Destroyer	Electrical, Stainless steel, Disposable syringe cum needle burne as per international standards, CE certified Warranty – 01 year	r
17	Medicine Trolley	With 4 wheel flat carrier with handle, 100 kg-500 kg capacity Warranty – 01 year	
18	Weight Machine Manual	Adult size, spring operated, Warranty – 01 year	
19	BP Instruments	Android and dial type, Warranty – 01 year	•
20	BP Instruments	Mercury type with portable stand, Warranty – 01 year	
21	Oxygen Cylinder Stand (trolley for cylinder)		4
22	Nebuliser Machine	For Children and Adults, Low noise compressor, Input AC1 220 V, 50/60 HZ, 350 mA, Max nebulizing rate >_ 0.2 ml/s Mass Median Diameter (MMD) 3.9 micrometre, Warranty – 01 year	00- nin,
23	Cautery Machine	Roated frequency- 450 khz Maximum HF power- 250 watt/500 ohms load Monopolar Coag-Max HF Power- 160 watt/ 500 ohms loa	d

/			
24	Valley lab force 40 cautery machine	Bipolar cut-Max HF power- 100 watt/ 150 ohms load Blend- Max HF power- 80 watt/ 125 ohms load Bipolar coag- Max HF power- 80watt/ 125 ohms load Electric Input- 230to 250VAC Output- 12 VAC Warranty – 01 year Automatic deactivation impedance -<20 ohms, >2000 ohms Automatic Activation impedance-40-100 ohms Time delay range- 1-5.1 second Activation tone- 45-65 dBA Alarm tone->65 dBA Operates on- 110/240 v, 50/60 HZ	
1		Dimension—7.8"Hx16.1"Wx11.9"D (199mmx409mmx303mm) Weight- 20lb (9.1 kg) Warranty – 01 year Height- 18" to 27" adjustable height with 4 legs	
25	Revolving Stainless Steel Stool	Material- Stainless Steel, Warranty – 01 year	
1 26	Laryngoscope with blade	Adult, Infant, Blade size-0,1,2,3,4, Warranty – 01 year	
27	Crash Cart Trolley	Stainless Steel Frame with Six Smooth Running ABS Centrally Lockable Drawers with Three Multipurpose Shelves. One Monitor Tray/platform made of Stainless Steel provided on Top at Eye Level. One Front Tray/Shelf made of Stainless Steel with Stainless Steel Side Safety Rails. One Lower Shelf fitted under ABS Drawers Set with Stainless Steel Side Safety Rails. One Handle provided on Side Trolley Frame. Stainless Steel Height Adjustable I.V. Rod with One I.V. Hook Provide on the back side of the frame. Six Handout Bins for keeping ampoules and injections etc. • Stainless Steel Cylinder Cage attachment for 'B' Type Oxygen Cylinder. Mobile on Four 125 High Strength Moulded PU Swivel Castors; Two with Brakes. Finish: Well Polished Stainless Steel, Warranty – 01 year	
28	Syringe Infusion Pump	 The Syringe pump should be programmable, user friendly, safe to use and should have battery backup and comprehensive alarm system. Must Work on commonly available standard 5ml/10m1/20ml/50ml/60m1 Syringes with accuracy of minimum of +/-2% or bener, with automatic syringe size recognition. Manufacturer should be ISO and European CE certified for quality standards. Flow rate programmable from 0.1 to 1000 ml/hr or more in steps of 0.1ml/hr with user selectable flow set rate option. SAVE last infusion rate even when the AC power is switched OFF. Bolus rate should be programmable to 40 to 1000 ml/hr or more with infused volume display and one key press bolus, auto 	

bolus as an advance feature with programmable bolus rate.

6. Display or Drug directory of more than 50 drugs, customized and adjustable.

7.Key board locking system for patient safety.

8.Keep Vein Open (KVO) must be available 1.0 ml/hr or set rate if lower than 1.0 ml. User

should have choice to disable KVO whenever desired.

9. Selectable Occlusion pressure trigger levels selectable from 300/500/900 mmHg.

10. Automatic detection of syringe size & proper fixing. Must provide alarm for wrong

loading of syringe such as flange out of slot; disengaged plunger, unsecured barrel etc.

11. Manual pusher with plunger protection guard.

12. Anti-bolus system to reduce pressure on sudden release of occlusion.

13. Should have comprehensive ALARM package including: Occlusion limit exceed alarm.

Near end of infusion pre-alarm & alarm, KVO rate flow Low battery pre-alarm and alarm, AC power failure, Drive disengaged and preventive maintenance.

14.Rechargeable Battery having at least 8 hours backup for about 5m1/hr flow rate with

50ml syringes. Larger battery life and indication of residual life will be preferred.

15. Docking Station for two or four pumps as per requirement so as to enable power up to 2-

4 pumps with one power cord when mounted on IV pole.

16. The unit shall be capable of stored and operating continuously in ambient temperature of

 $10\ 50 deg\ C$ and relative humidity of 15-90%.

17. Power input to be 220-240V AC, 50 Hz.

18. Warranty – 01 year

Superintendent in Sahood Lagman Rayak Medical Collete Koraput, Odisha